

To return to ADCED's webpages on Local Ordinances Governing Nonpoint Source Pollution in Alaska, please use the "back" function on your web browser or click this link: <http://www.dced.state.ak.us/dca/nonpoint/nonpoint.htm>

KENAI PENINSULA BOROUGH CODE OF ORDINANCES

14.06.150. Road construction standards--Drainage and culvert material.

Roads shall be constructed to prevent ponding of runoff waters in roadside ditches. Drainage ditches shall be constructed such that runoff waters will be conveyed to natural drainage courses, ditches or waterways, or other man-made drainage courses. Outfalls shall be constructed to prevent excessive siltation of riparian habitats, channel erosion or other drainage to public or private property. The RSA Board may require engineering analysis and design for locations susceptible to flooding, excessive siltation, or other natural conditions potentially damaging to the right-of-way, adjacent property, or water courses and water bodies. A roadway cross culvert shall be minimum diameter of 18 inches and driveway culverts shall be a minimum of 12 inches. Culverts, coupling bands and special sections shall be corrugated steel pipe, with a minimum of 16 gauge. Plastic culverts are acceptable if they meet AASHTO Standard Section 706-2.07 corrugated polyethylene pipe, AASHTO M 294, Type S.

(Ord. No. 2001-06, § 3, 4-17-01)

To return to ADCED's webpages on Local Ordinances Governing Nonpoint Source Pollution in Alaska, please use the "back" function on your web browser or click this link: <http://www.dced.state.ak.us/dca/nonpoint/nonpoint.htm>